

POWERSENTRY 6000

A RUGGED PORTABLE OR PERMANENT SURVEILLANCE SOLUTION

The Power Sentry 6000 is easily mounted with a universal bracketing system on light poles and sides of buildings/structures. Hang it on a building parapet or even set it up on a tripod.

KEY FEATURES

- **Unique Remote Management Monitoring and Control Through Our MP Status Technology**
Manage inputs/outputs for lighting/LED lighting, audio, GPS and a sophisticated battery charging system.
- **Numerous Mounting Options for Easy Deployment**
The PowerSentry 6000 allows for plug-n-play operation, and is easily mounted on pole, a wall or tripod, or can be easily hooked over a fence or roof parapet. Just power up and go!
- **Superior Mobility**
Easily installs in areas where it's needed the most. Put video surveillance and/or communication technologies right where you want them, right when you need them.
- **Dependability You Can Count On**
 - The PowerSentry 6000 is an EDGE device, which means that recorded images are stored within the PowerSentry 6000 itself, allowing you to avoid the demands of larger amounts of bandwidth.
 - Its battery pack charges at night so you can rely on 24/7 power. It will run even if the structure it's mounted to, such as a light pole, has temporary or scheduled power.
- **Sleek Design Keeps Your Projects Discreet**
The PowerSentry will blend into the surroundings, but can be customized and made noticeable, if necessary, as a routine deterrent.

- **Perfect for Areas with "Scheduled" or "Timed" Power Availability - Charges at Night for 24/7 Usage**
Avoids traditional installation power obstacles and substantially reduces the cost of deploying our various technologies in ways not previously available.
- **Minimizes Re-Wiring**
Accepts 90 - 277 Volt AC input

OPTIONS

- Network Camera Outdoor rates with:
 - Pan, tilt and zoom (PTZ) and/or fixed
 - Day/night switching
- Variety of battery pack sizes
- Long-lasting and efficient lithium battery packages
- Customizable with LED lighting, labeling, and more



651-434-2333

250 Lothenbach Avenue, West St Paul, MN 55118

www.mobileprosystems.com



POWERSENTRY 6000 SPECIFICATIONS

SPECIFICATIONS

- Rugged aluminum structure
- 9" x 9" x 21" minimum length (length varies with the amount of optional backup battery capabilities chosen)
- Plug-in 110 VAC power with optional battery charging

OPTIONS

Communications

- Cellular, mesh network, Wi-Fi 802.11, 900 MHZ, fiber or copper connection

Power

- 110 VAC charge and battery backup (90 - 277 VAC)
 - Battery packs: Lithium-based and lead acid options, multiple sizes available

Power Inputs

- Accepts 90 - 277 VAC

Cameras

- IP networking-based fixed position, optional upgrade to a pan, tilt and zoon (PTZ) dome style, high definition, day/night, AT THE EDGE video storage, outdoor, environment enclosure

Recording

- On-board EDGE video storage and video management available as standard configuration

Deterrents

- Strobe lights, horns, sirens, audio and customized color

Remote Viewing

- Available through both network and cellular communications

